

Specialty & Hand-Held

Additional info for LAP65-30,

LAP65-60, LAP65-100

- Ideal for repetitive labeling of boxes or bags
- Simply squeeze handle to dispense and apply any die-cut label
- Maximum outside diameter of roll 3.93" (100mm)
- No custom tooled slots needed to dispense labels, just a 1/8" (3mm) gap between labels
- Manufactured for industrial use
- Unique sensor automatically adjusts the label stroke
- Patented mechanism dispenses virtually any shape of die-cut label

Additional info for LDHANGTAB

- Will dispense labels and die-cut parts
- Adjustable strip plate for hard-to-release hang tabs
- Will accommodate core sizes from 1" to 6" (25 to 152mm)
- Automatically rewinds liner scrap for a cleaner working environment
- Liner scrap is easily removed
- No tools required for adjusting to different size hang-tabs
- No maintenance required
- Will dispense clear or opaque hang-tabs

For 230V machines, please add "-2" to the end of the model number. (Example: LDHANGTAB-2)

LR4500

Label Rewinder

- Rewind labels from thermal transfer printers or reels
- 2 speeds (slow and fast)
- Bi-directional (forward and backward)
- Maximum material width 4.5" (114mm)
- Maximum outside diameter of roll 9" (251mm)
- Use 2 LR4500's to unwind and rewind labels for proper orientation of labels



*SHOWN WITH A BRADY IP PRINTER SYSTEM



LAP65-30

Manual Hand-Held Label Applicator

- Maximum label width 1.20" (30mm)
- Maximum label length 2.36" (60mm)
- Minimum core size 1" (25mm)



LAP65-60

Manual Hand-Held Label Applicator

- Maximum label width 2.36" (60mm)
- Maximum label length 2.36" (60mm)
- Minimum core size 1" (25mm)



LAP65-100

Manual Hand-Held Label Applicator

- Maximum label width 3.93" (100mm)
- Maximum label length 2.36" (60mm)
- Minimum core size 1" (25mm)

LDHANGTAB

Electric Hang-Tab Dispenser

- Automatically peels and advances labels
- Photosensor accuracy and reliability
- All metal construction
- High torque motor for heavy rolls of labels
- Will dispense hang-tabs from .25" to 4.5" (6 to 114mm) wide
- Will dispense hang-tabs from .125" to 6" (3 to 152mm) in length



MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed*	Core	Dimensions	Electrical Requirements	Weight
LR4500	.25" to 4.5" (6mm to 114mm)	Variable	9" (251mm)	Slow/Fast	1.25" & 3"	11" (L) x 6" (W) x 9.2" (H) 27.9cm (L) x 15.2cm (W) x 23.4cm (H)	12V Dc with Universal transformer, 100V - 240V	8.5 lbs (3.6 kg)

*speed calculated at 60 Hz

MODEL #	Max. Outside Dia. of Roll	Minimum Core Size	Liner Maximum Width	Liner Minimum Width	Maximum Label Length	Minimum Label Length	Weight
LAP65-30	3.93" (100mm)	1" (25mm)	1.20" (30mm)	.75" (19mm)	2.36" (60mm)	.78" (20mm)	11.2 oz (318 g)
LAP65-60	3.93" (100mm)	1" (25mm)	2.36" (60mm)	1" (25mm)	2.36" (60mm)	.78" (20mm)	13.1 oz. (372 g)
LAP65-100	3.93" (100mm)	1" (25mm)	3.96" (100mm)	2.15" (55mm)	2.36" (60mm)	.78" (20mm)	15.0 oz (425 g)

MODEL #	Liner Capacity Width	Length	Roll Capacity	Feed Speed*	Core	Dimensions	Electrical Requirements	Weight
LDHANGTAB	.25" to 4.5" (6mm to 114mm)	.125" to 6" (3mm to 152mm)	16" (408mm)	3.3"/sec* (8cm/sec)	6" (153mm)	10.8"(L) x 10.8"(W) x 14.5"(H) 27.4cm(L) x 27.4cm(W) x 36.8cm(H)	100/120V 50/60Hz, <1 amp (230V 50/60Hz CE available) (4.76 kg)	9.5 lbs (4.3 kg)

*speed calculated at 60 Hz